

View Online at <https://aerobasegroup.com/nsn/5340-01-253-3033>

Fabrication Method (non-core):

Extruded

Mounting Hole Type:

Plain

First Leg Length:

0.750 inches

Second Leg Length:

Between 0.750 inches and 0.780 inches

Second Leg Width:

Between 1.480 inches and 1.520 inches

Second Leg Corner Radius:

Between 0.220 inches and 0.280 inches

First Leg Hole Diameter:

0.129 inches

Second Leg Hole Diameter:

Between 0.263 inches and 0.266 inches

Second Leg Distance Between Hole Centers Along Width:

1.000 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.230 inches and 0.250 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.220 inches and 0.280 inches

First Leg Thickness:

0.063 inches

Second Leg Thickness:

0.063 inches

First Leg Width:

Between 1.480 inches and 1.520 inches

First Leg Corner Radius:

Between 0.220 inches and 0.280 inches

First Leg Distance Between First And Second Hole Centers Along Width:

Between 0.490 inches and 0.510 inches

First Leg Distance Between Second And Third Hole Centers Along Width:

Between 0.490 inches and 0.510 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.240 inches and 0.260 inches

First Leg Distance From Edge To Hole Center Along Length:

0.250 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Three holes

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Two holes

Features Provided:

Nut

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Left hand nut

Material:

Aluminum alloy 2024 or aluminum alloy 1230

Material Specification:

Qq-a-200/3, t8511 federal specification 1st material response or qq-a-250/5 federal specification all material responses

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-a-8625 spec.