

View Online at <https://aerobasegroup.com/nsn/5340-01-253-3756>

Mounting Hole Type:

Plain

First Leg Length:

0.460 inches

Second Leg Length:

0.530 inches

Second Leg Width:

2.250 inches

First Leg Hole Diameter:

Between 0.145 inches and 0.151 inches

Second Leg Hole Diameter:

Between 0.229 inches and 0.239 inches

Second Leg Distance Between Hole Centers Along Length:

0.125 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

0.360 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.450 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.155 inches

First Leg Thickness:

0.032 inches

Second Leg Thickness:

0.032 inches

First Leg Width:

2.560 inches

First Leg Distance Between Hole Centers Along Width:

2.250 inches

First Leg Distance From Edge To Hole Center Along Width:

0.140 inches

First Leg Distance From Edge To Hole Center Along Length:

0.200 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

First leg is cut out at bend; six mounting holes equally spaced at 0.360 in. On second leg

Material:

Copper alloy 102 or copper alloy 105 or copper alloy 110 or copper alloy 116 or copper alloy 122 or copper alloy 125 or copper alloy

Material Specification:

Qq-c-576, 1/2 h federal specification all material responses

Surface Treatment:

Tin

Surface Treatment Specification:

Mil-t-10727 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-t-10727 spec.