## NSN 5340-01-253-6662

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-253-6662

Firs	+ 1	DΩ	l an	ath	٠.
FILE	it L	.eu	Len	atn	١.

Between 0.690 inches and 0.710 inches

Second Leg Length:

Between 0.615 inches and 0.635 inches

Second Leg Width:

Between 0.615 inches and 0.635 inches

First Leg Slot Length:

Between 0.390 inches and 0.410 inches

First Leg Slot Width:

Between 0.151 inches and 0.161 inches

Second Leg Distance Between Hole Centers Along Width:

Between 0.345 inches and 0.355 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.128 inches and 0.148 inches

Second Leg Slot Length:

Between 0.340 inches and 0.360 inches

Second Leg Slot Width:

Between 0.120 inches and 0.130 inches

First Leg Width:

Between 0.615 inches and 0.635 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.302 inches and 0.322 inches

First Leg Style:

Square

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

2 slots

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

0.020 radians

Material:

Plastic acetal

**Material Specification:** 

Mil-p-46137 military specification single material response

**Style Designator:** 

Angle

Shelf Life:

N/a

**Unit Of Measure:** 

--

## NSN 5340-01-253-6662

Angle Bracket - Page 2 of 2



Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-p-46137 spec.