

View Online at <https://aerobasegroup.com/nsn/5340-01-254-1405>

**Mounting Hole Type:**

Plain

**First Leg Length:**

0.750 inches

**Second Leg Length:**

1.000 inches

**Second Leg Width:**

0.688 inches

**First Leg Hole Diameter:**

Between 0.152 inches and 0.157 inches

**Second Leg Hole Diameter:**

Between 0.500 inches and 0.505 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.688 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.625 inches

**First Leg Thickness:**

0.062 inches

**Second Leg Thickness:**

0.062 inches

**First Leg Width:**

1.375 inches

**First Leg Distance Between Hole Centers Along Width:**

1.000 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.188 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.375 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Chamfered ends

**Second Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Second Leg Chamfer Angle:**

45.0 degrees

**Special Features:**

Second leg hole has 2 projected cutouts, 1 cutout 0.188 in. W, extends from hole edge to side, 1 cutout 0.095 in. W extends to 0.313 in.

From edge

**Material:**

Aluminum alloy 6063

**Material Specification:**

Qq-a-200/9, t52 federal specification single material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625, type i, cl 1 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-a-8625 spec.