

View Online at <https://aerobasegroup.com/nsn/5340-01-254-6544>

Mounting Hole Type:

Plain

First Leg Length:

2.500 inches

Second Leg Length:

2.500 inches

Second Leg Width:

7.500 inches

First Leg Slot Length:

Between 1.000 inches and 1.060 inches

First Leg Slot Width:

Between 0.531 inches and 0.561 inches

Second Leg Distance Between Hole Centers Along Width:

6.000 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.750 inches

Second Leg Distance From Edge To Hole Center Along Length:

1.000 inches

Second Leg Slot Length:

Between 1.000 inches and 1.060 inches

Second Leg Slot Width:

Between 0.531 inches and 0.561 inches

First Leg Thickness:

0.375 inches

Second Leg Thickness:

0.375 inches

First Leg Width:

7.500 inches

First Leg Distance Between Hole Centers Along Width:

4.000 inches

First Leg Distance From Edge To Hole Center Along Width:

1.500 inches

First Leg Distance From Edge To Hole Center Along Length:

1.000 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

2 slots

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

2 slots

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Aluminum alloy 5083 or aluminum alloy 5086

Material Specification:

Qq-a-200/4 federal specification 1st material response or qq-a-200/5 federal specification 2nd material response

Surface Treatment:

Primer epoxy and plastic polyurethane

Surface Treatment Specification:

Mil-p-23377 military standard 1st treatment response and mil-c-46168 military standard 1st treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-p-23377 spec.