

View Online at <https://aerobasegroup.com/nsn/5340-01-254-6544>

**Mounting Hole Type:**

Plain

**First Leg Length:**

2.500 inches

**Second Leg Length:**

2.500 inches

**Second Leg Width:**

7.500 inches

**First Leg Slot Length:**

Between 1.000 inches and 1.060 inches

**First Leg Slot Width:**

Between 0.531 inches and 0.561 inches

**Second Leg Distance Between Hole Centers Along Width:**

6.000 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.750 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

1.000 inches

**Second Leg Slot Length:**

Between 1.000 inches and 1.060 inches

**Second Leg Slot Width:**

Between 0.531 inches and 0.561 inches

**First Leg Thickness:**

0.375 inches

**Second Leg Thickness:**

0.375 inches

**First Leg Width:**

7.500 inches

**First Leg Distance Between Hole Centers Along Width:**

4.000 inches

**First Leg Distance From Edge To Hole Center Along Width:**

1.500 inches

**First Leg Distance From Edge To Hole Center Along Length:**

1.000 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

2 slots

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

2 slots

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Material:**

Aluminum alloy 5083 or aluminum alloy 5086

**Material Specification:**

Qq-a-200/4 federal specification 1st material response or qq-a-200/5 federal specification 2nd material response

**Surface Treatment:**

Primer epoxy and plastic polyurethane

**Surface Treatment Specification:**

Mil-p-23377 military standard 1st treatment response and mil-c-46168 military standard 1st treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0

**Mil-std (military Standard):**

Mil-p-23377 spec.