

View Online at <https://aerobasegroup.com/nsn/5340-01-255-5933>

Material Thickness:

0.250 inches

Mounting Hole Type:

Plain

First Leg Length:

2.500 inches

Second Leg Length:

2.760 inches

Second Leg Width:

0.750 inches

First Leg Hole Diameter:

0.250 inches

Second Leg Hole Diameter:

0.380 inches

Second Leg Distance Between Hole Centers Along Length:

2.000 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.380 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.380 inches

First Leg Width:

1.125 inches

First Leg Distance From Edge To Hole Center Along Width:

0.250 inches

First Leg Distance From Edge To Hole Center Along Length:

0.250 inches

First Leg End Radius:

0.250 inches

Second Leg End Radius:

0.375 inches

First Leg Style:

End radius and tapered

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

Two holes

Hole Quantity:

3

Angle:

75.0 degrees

Second Leg Relationship To First Leg:

Not identical

Special Features:

Inside edge second leg chamfered 2 places 45 degrees x 0.030 x 1.120 lg andbrinnell hardness 246-280

Material:

Steel comp 4130 or steel comp 4140

Material Specification:

Qq-s-635 federal specification all material responses

Surface Treatment:

Phosphate zinc

Surface Treatment Specification:

Mil-std-171 fn 5.3.2.3 military standard single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-std-171 spec.