

View Online at <https://aerobasegroup.com/nsn/5340-01-257-4369>

Mounting Hole Type:

Plain

First Leg Length:

0.950 inches

Second Leg Length:

4.000 inches

First Leg Hole Diameter:

0.414 inches

Second Leg Distance From Edge To Hole Center Along Width:

1.350 inches

Second Leg Distance From Edge To Hole Center Along Length:

1.875 inches

Second Leg Slot Length:

2.250 inches

Second Leg Slot Width:

1.000 inches

First Leg Thickness:

Between 0.360 inches and 0.400 inches

Second Leg Thickness:

Between 0.360 inches and 0.400 inches

First Leg Width:

3.900 inches

First Leg Distance Between Hole Centers Along Width:

3.000 inches

First Leg Distance From Edge To Hole Center Along Width:

0.450 inches

First Leg Distance From Edge To Hole Center Along Length:

0.450 inches

Second Leg End Radius:

1.250 inches

First Leg Style:

Cut out

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

End radius and tapered

Second Leg Hole Arrangement Style:

One slot

Second Leg Relationship To First Leg:

Not identical

Material:

Steel comp 1141 or steel comp 4140 or steel comp 4130

Material Specification:

Sae assn standard all material responses

Surface Treatment:

Zinc

Surface Treatment Specification:

Gm 4342-m code 30440, caged 73342 mfr ref single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0