

View Online at <https://aerobasegroup.com/nsn/5340-01-257-5170>

**Cross Sectional Shape:**

Flat

**Hole Diameter:**

Between 0.2501 inches and 0.2507 inches

**Edge Shape:**

Rectangle, multi holes

**Length:**

41.550 inches

**Hole Quantity Along Length:**

14

**Hole Quantity Along Width:**

10

**Distance Between Holes Along Length:**

1.020 inches and 5.000 inches and 6.790 inches and 7.766 inches

**Distance From First Hole Centerline To End Along Length:**

2.380 inches

**Body Thickness:**

0.090 inches

**Securing Device Type:**

Special

**Mounting Opening Shape Style:**

Unthreaded hole

**Features Provided:**

Observation facility and special marking

**Special Features:**

Mtg holes csk 0.400 x 100 degrees requiring 18 stud nuts p/n 805233-4, 6 stud nuts p/n 805233-1 and rings p/n 534884-1; item has insulation p/n 29034951, 1 window w/dia 1.250 to 1.310 in., p/n 2903499-1, 4 mtg holes 0.116 in. Csk 0.18 x 82 degrees requiring 4 screws p/n ms51959-2; has "warning" decal, p/n 2902331-15, located 20.80 in. Porm 0.50 in. From lft edge along lg, also has a "charging pressure" decal p/n 2795164-1 & "caution" decal p/n 277684-6

**Material:**

Aluminum alloy 6061

**Material Specification:**

Qq-a-250/11 tem t6 federal specification single material response

**Surface Treatment:**

Plastic

**Surface Treatment Specification:**

Mil-c-83286, type 1 color no. 36270 military specification single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A531c0

**Mil-std (military Standard):**

Mil-c-83286 spec.