

View Online at <https://aerobasegroup.com/nsn/5340-01-258-4684>

First Leg Length:

1.620 inches

Second Leg Length:

11.875 inches

Second Leg Width:

2.000 inches

Second Leg End Width:

1.500 inches

First Leg Slot Length:

1.000 inches

First Leg Slot Width:

Between 0.420 inches and 0.460 inches

Second Leg Distance From Edge To Hole Center Along Width:

1.000 inches

Second Leg Distance From Edge To Hole Center Along Length:

2.220 inches

Second Leg Slot Length:

2.500 inches

Second Leg Slot Width:

0.312 inches

First Leg Thickness:

0.375 inches

Second Leg Thickness:

0.375 inches

First Leg Width:

2.000 inches

First Leg End Width:

1.500 inches

First Leg Distance From Edge To Hole Center Along Width:

1.000 inches

First Leg Distance From Edge To Hole Center Along Length:

0.685 inches

First Leg Style:

Chamfered ends

First Leg Hole Arrangement Style:

One slot

Second Leg Style:

Chamfered ends

Second Leg Hole Arrangement Style:

One slot

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

First Leg Chamfer Angle:

45.0 degrees

Second Leg Chamfer Angle:

45.0 degrees

Special Features:

Additional slot on second leg 3.750 in. Lg by 0.312 in. Wide; color green number 24533 if enamel finish or light green if lacquer finish

Material:

Aluminum alloy 2024 or aluminum alloy 5086 or aluminum alloy 5083

Surface Treatment:

Enamel semigloss or lacquer

Surface Treatment Specification:

Tt-e-529, cla federal specification 1st treatment response or mil-l-52043 military specification 2nd treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A042a0

Mil-std (military Standard):

Mil-l-52043 spec.