## NSN 5340-01-259-0502

Block Clamp - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-259-0502

Over	all I	en	ath:
~~~	an L	-611	иит.

Between 5.500 inches and 5.780 inches

**Overall Height:** 

Between 0.915 inches and 1.045 inches

Overall Width:

Between 1.400 inches and 1.500 inches

**Mounting Hole Diameter:** 

Between 0.334 inches and 0.354 inches

**Mounting Hole Quantity:** 

3

**Distance From Center Of Mounting Hole To Edge Along The Width:** 

Between 0.480 inches and 0.520 inches

**Center To Center Distance Between First And Second Mounting Holes:** 

1.500 inches

**Center To Center Distance Between First And Third Mounting Holes:** 

3.000 inches

**Mounting Facility:** 

Unthreaded hole

**Block Height:** 

Between 0.670 inches and 0.770 inches

**Clamping Hole Quantity:** 

4

**Distance From End To First Mounting Hole Center:** 

Between 1.280 inches and 1.380 inches

**Distance From End To First Clamping Hole Center:** 

Between 0.580 inches and 0.630 inches

Center To Center Distance Between First And Sixth Clamping Holes:

4.500 inches

Material:

Aluminum

**Material Specification:** 

Qq-a-250/2 federal specification single material response

**Surface Treatment:** 

Anodize

**Surface Treatment Specification:** 

Mil-a-8625, ty2, cl1 military specification single treatment response

**Style Designator:** 

Rectangular

Shelf Life:

N/a

**Unit Of Measure:** 

--

## NSN 5340-01-259-0502

Block Clamp - Page 2 of 2



Demilitarization:

No

Fiig:

A105a0

Mil-std (military Standard):

Mil-a-8625 spec.