

View Online at <https://aerobasegroup.com/nsn/5340-01-259-2476>

Mounting Hole Type:

Threaded

First Leg Length:

1.000 inches

Second Leg Length:

2.750 inches

Reinforcement Method (non-core):

Gusset both legs

Second Leg Width:

4.875 inches

Second Leg Hole Diameter:

0.3125 inches

Second Leg Distance Between Hole Centers Along Width:

3.000 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.938 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.500 inches

First Leg Thickness:

0.350 inches

Second Leg Thickness:

0.330 inches

Center Section Height:

4.480 inches

Center Section Width:

4.875 inches

First Leg Width:

4.875 inches

First Leg Distance Between Hole Centers Along Width:

3.000 inches

First Leg Distance From Edge To Hole Center Along Width:

0.938 inches

First Leg Distance From Edge To Hole Center Along Length:

0.212 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Cut out

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Angle:

90.0 degrees

Second Leg Cutout Length:

1.750 inches

Second Leg Cutout Width:

4.000 inches

Special Features:

2nd leg cutout opposite direction; item color black

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-250/11, t6 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, cl 2, type 2 military specification single treatment response

Style Designator:

Adjacent angles

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-a-8625 spec.