

View Online at <https://aerobasegroup.com/nsn/5340-01-259-2477>

Mounting Hole Type:

Plain

First Leg Length:

1.420 inches

Second Leg Length:

2.810 inches

Second Leg Width:

1.000 inches

Second Leg End Width:

0.620 inches

First Leg Hole Diameter:

Between 0.376 inches and 0.460 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.500 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.745 inches

Second Leg Slot Length:

0.750 inches

Second Leg Slot Width:

Between 0.376 inches and 0.460 inches

First Leg Thickness:

0.190 inches

Second Leg Thickness:

0.190 inches

Center Section Height:

2.380 inches

Center Section Width:

1.000 inches

Center Section Thickness:

0.190 inches

First Leg Width:

1.000 inches

First Leg End Width:

0.620 inches

First Leg Distance From Edge To Hole Center Along Width:

0.500 inches

First Leg Distance From Edge To Hole Center Along Length:

0.500 inches

First Leg Style:

Chamfered ends

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Chamfered ends

Second Leg Hole Arrangement Style:

One slot

Second Leg Relationship To First Leg:

Not identical

First Leg Chamfer Angle:

45.0 degrees

Second Leg Chamfer Angle:

45.0 degrees

Material:

Aluminum alloy 5083 or aluminum alloy 5086

Material Specification:

Qq-a-250/6, h321 federal specification 1st material response or qq-a-250/6, h323 federal specification 1st material response or qq-a-250/7, h32 federal specification 2nd material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541, cl 1a military specification single treatment response

Style Designator:

Double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.