NSN 5340-01-259-2477

Double Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-259-2477

Mounting Hole Type:
Plain
First Leg Length:
1.420 inches
Second Leg Length:
2.810 inches
Second Leg Width:
1.000 inches
Second Leg End Width:
0.620 inches
First Leg Hole Diameter:
Between 0.376 inches and 0.460 inches
Second Leg Distance From Edge To Hole Center Along Width:
0.500 inches
Second Leg Distance From Edge To Hole Center Along Length:
0.745 inches
Second Leg Slot Length:
0.750 inches
Second Leg Slot Width:
Between 0.376 inches and 0.460 inches
First Leg Thickness:
0.190 inches
Second Leg Thickness:
0.190 inches
Center Section Height:
2.380 inches
Center Section Width:
1.000 inches
Center Section Thickness:
0.190 inches
First Leg Width:
1.000 inches
First Leg End Width:
0.620 inches
First Leg Distance From Edge To Hole Center Along Width:
0.500 inches
First Leg Distance From Edge To Hole Center Along Length:
0.500 inches
First Leg Style:
Chamfered ends
First Leg Hole Arrangement Style:
One hole

One hole

NSN 5340-01-259-2477

Double Angle Bracket - Page 2 of 2



Second Leg Style:
Chamfered ends
Second Leg Hole Arrangement Style:
One slot
Second Leg Relationship To First Leg:
Not identical
First Leg Chamfer Angle:
45.0 degrees
Second Leg Chamfer Angle:
45.0 degrees
Material:
Aluminum alloy 5083 or aluminum alloy 5086
Material Specification:
Qq-a-250/6, h321 federal specification 1st material response or qq-a-250/6, h323 federal specification 1st material response or qq-a-250/7,
n32 federal specification 2nd material response
Surface Treatment:
Chromate
Surface Treatment Specification:
Mil-c-5541, cl 1a military specification single treatment response
Style Designator:
Double angle
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
A042a0
Mil-std (military Standard):
Mil-c-5541 spec.