

View Online at <https://aerobasegroup.com/nsn/5340-01-259-5687>

**Securing Device Type:**

Special and threaded fastener

**Mounting Opening Shape Style:**

Unthreaded hole

**Features Provided:**

Special marking

**Special Features:**

Irreg shape, has 2 holes 0.375 cbore 0.040 dp, 0.089 (no. 43) 0.11 x 90 degrees csk 0.112- 40 unc-2b 0.140 cbore 0.050 dp farside; 18 holes 0.089 (no.43) 0.11 x 90 degrees csk 0.112- 40 unc-2b 0.140 cbore 0.050 dp far side; 3 holes diameter 0.190 in.; 18 holes 0.120 (no. 31) 0.250 dp 0.16 x 120 degrees csk 0.112-40 unc-2b helical coil thds 0.140 in. Dp, requiring 18 inserts p/n ms 122076; has 4 warning decals, 1 decal p/n 290233-7 located 5.250 in. Porm 0.100 in. From edge along lg, 1 decal p/n 290331-9 located 4.100 in. Porm 0.100 in. From edge along width, 1 decal p/n 2902331-12 located 1.600 in. Porm 0.100 in. From edge along lg & 9.250 in. From edge along width, 1 decal p/n 2902331-16 located 6.400 in. Porm 0.100 in. From edge along width & 1.600 in. Porm 0.100 in. From edge along lg; item has addtl impregnation process per mil-std-276 (f-74, method 05, using 30 psi for 10 minutes)

**Surface Treatment:**

Chromate and primer and paint

**Surface Treatment Specification:**

Mil-c-5541, cl 3 military specification 1st treatment response and tt-p-1757, clr y federal specification 2nd treatment response and mil-c-22750, type 1, cl 1 color no. 36231 military specification 3rd treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A531c0

**Mil-std (military Standard):**

Mil-std-276 spec.