

View Online at <https://aerobasegroup.com/nsn/5340-01-259-7832>

Mounting Hole Type:

Countersunk and plain

First Leg Length:

2.000 inches

Second Leg Length:

2.180 inches

Reinforcement Method (non-core):

Gusset both legs

Second Leg Width:

2.680 inches

Second Leg Corner Radius:

0.500 inches

First Leg Hole Diameter:

0.281 inches

Second Leg Hole Diameter:

1.160 inches

Second Leg Distance Between Hole Centers Along Width:

0.718 inches

Second Leg Distance Between Hole Centers Along Length:

0.718 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.212 inches

First Leg Thickness:

0.050 inches

Second Leg Thickness:

0.050 inches

First Leg Width:

2.680 inches

First Leg Corner Radius:

0.370 inches

First Leg Distance Between Hole Centers Along Width:

1.780 inches

First Leg Distance Between Hole Centers Along Length:

1.000 inches

First Leg Distance From Edge To Hole Center Along Width:

0.500 inches

First Leg Distance From Edge To Hole Center Along Length:

0.370 inches

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Plate on first leg; 0.123 in. Diameter hole on second leg

Material:

Aluminum alloy 7075

Material Specification:

Qq-a-250/13, t6 federal specification single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A042a0