

View Online at <https://aerobasegroup.com/nsn/5340-01-262-3861>

Mounting Hole Type:

Plain

Second Leg Width:

1.500 inches

Second Leg Corner Radius:

0.250 inches

Second Leg Hole Diameter:

Between 0.220 inches and 0.230 inches

Second Leg Distance Between Hole Centers Along Width:

0.050 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.250 inches

First Leg Thickness:

0.050 inches

Second Leg Thickness:

0.050 inches

Center Section Height:

0.500 inches

Center Section Width:

1.500 inches

Center Section Thickness:

0.050 inches

First Leg Width:

1.500 inches

First Leg Corner Radius:

0.250 inches

First Leg Distance Between Hole Centers Along Width:

1.000 inches

First Leg Distance From Edge To Hole Center Along Width:

0.250 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

No hole

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Angle:

90.0 degrees

Special Features:

Attached with rivets; requires clip nut, lh position; intend for support of wire bundles only

Material:

Aluminum alloy 2024

Material Specification:

Qq-a-250/5, t81 federal specification single material response

Surface Treatment:

Primer and chromate

Surface Treatment Specification:

Mil-p-23377 military specification 1st treatment response and mil-c-5541 military specification 2nd treatment response

Style Designator:

Double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-p-23377 spec.