NSN 5340-01-262-4160

Double Angle Bracket - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5340-01-262-4160 |
|---|
| Mounting Hole Type: |
| Plain |
| First Leg Length: |
| Between 1.141 inches and 1.171 inches |
| Second Leg Length: |
| Between 1.141 inches and 1.171 inches |
| End Application: |
| Sacdin maintenance |
| First Leg Hole Diameter: |
| 0.093 inches |
| First Leg Thickness: |
| 0.063 inches |
| Second Leg Thickness: |
| 0.063 inches |
| Center Section Height: |
| Between 1.675 inches and 1.705 inches |
| Center Section Thickness: |
| 0.063 inches |
| First Leg Distance Between Hole Centers Along Width: |
| 1.375 inches |
| First Leg Distance Between Hole Centers Along Length: |
| 0.937 inches |
| First Leg Distance From Edge To Hole Center Along Width: |
| Between 0.119 inches and 0.134 inches |
| First Leg Distance From Edge To Hole Center Along Length: |
| Between 0.102 inches and 0.117 inches |
| First Leg Style: |
| Corner radius |
| First Leg Hole Arrangement Style: |
| Four holes |
| Second Leg Relationship To First Leg: |
| Identical |
| Material: |
| Aluminum alloy 3003 |
| Material Specification: |
| Qq-a-359 federal specification single material response |
| Surface Treatment: |
| Anodize |
| Surface Treatment Specification: |
| Mil-a-8625 military specification single treatment response |

Style Designator: Adjacent angles

NSN 5340-01-262-4160

Double Angle Bracket - Page 2 of 2



| N/a |
|-------------------|
| Unit Of Measure: |
| |
| Damilitarination. |

Shelf Life:

Demilitarization:

No

Fiig: A042a0

Mil-std (military Standard):

Mil-a-8625 spec.