NSN 5340-01-262-4460

Extension Drawer Slide - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5340-01-262-4460

With: 0.750 inches Excended Length: 20.745 inches Mounting Method: Threaded hole Side For Which Designed: Left hand Closed Length: 14.125 inches Special Features: Has 2 hole diameter 0.374 to 0.381 in., w/ 0.375 in. Distance from edge to hole cntr along width, 1.250 in. Distance from edge to hole cntr along uidth, 1.250 in. Distance from edge to hole cntr along width, 0.750 in. Fsc Application Data: An/uxc-4 Sheff Life: N/a Uid Measure: - Demilitarization: No Fig: AN/uxC-1 Damilitarization: An/uxC-2 Sheff Life: N/a Sheff Life: <	
Extended Length: 20.745 inches Mounting Method: Threaded hole Bide For Which Designed: Let hand Cosed Length: 14.125 inches Special Features: 14.325 hole diameter 0.374 to 0.381 in., w/ 0.375 in. Distance form edge to hole cntr along width, 1.250 in. Distance form edge to hole cntr along width, 1.250 in. Distance form edge to hole cntr along width, 0.750 in. Vidta Output: Anvace4 Sheft Life: Na Lift Of Measure: Image: No Formiltarization: No Fig:	Width:
20.745 inches Mounting Method: Threaded hole Side For Which Designed: Left hand Closed Length: 14.125 inches Special Features: Has 2 hole diameter 0.374 to 0.381 in., w/ 0.375 in. Distance from edge to hole cntr along width, 1.250 in. Distance from edge to hole cntr along width, 1.250 in. Distance from edge to hole cntr along width, 0.750 in. Yaca A hole Anfuxce-4 Phell Life: N/a Lift Of Measure: Image: No Fig:	0.750 inches
Hounting Method: Threaded hole Side For Which Designed: Left hand Closed Length: 14.125 inches Special Features: Has 2 hole diameter 0.374 to 0.381 in., w/ 0.375 in. Distance from edge to hole cntr along width, 1.250 in. Distance from edge to hole cntr along width, 1.250 in. Distance from edge to hole cntr along width, 1.250 in. Distance from edge to hole cntr along width, 1.250 in. Distance from edge to hole cntr along width, 0.750 in. Vidth, 0.750 in. Fose Application Data: An/uxc-4 Phelf Life: N/a Int Of Measure: Imitiatization: No Fig:	Extended Length:
Threade hole Side For Which Designed: Left hand Closed Length: 14.125 inches Special Features: Has 2 hole diameter 0.374 to 0.381 in., w/ 0.375 in. Distance from edge to hole cntr along width, 1.250 in. Distance from edge to hole cntr along width, 1.250 in. Distance from edge to hole cntr along lg & 2.000 in. Distance btwn hole cntrs; 4 holes diameter 0.165 to 0.171 in. Csk to diameter 0.284 x 100 degrees w/ c to c dist, along width, 0.750 in. Fsc Application Data: An/uxc-4 Sheft Life: Iva Iva of Measure: - Penilitarization: No Fig:	20.745 inches
Side For Which Designed: Left hand Closed Length: 14.125 inches Special Features: 14.32 hole diameter 0.374 to 0.381 in., w/ 0.375 in. Distance from edge to hole cntr along width, 1.250 in. Distance from edge to hole cntr along width, 1.250 in. Distance from edge to hole cntr along width, 0.750 in. 14.32 hole diameter 0.374 to 0.381 in., w/ 0.375 in. Distance from edge to hole cntr along width, 1.250 in. Distance from edge to hole cntr along width, 0.750 in. 14.02 hole diameter 0.374 to 0.381 in., w/ 0.375 in. Distance from edge to hole cntr along width, 1.250 in. Distance from edge to hole cntr along width, 0.750 in. 14.02 hole diameter 0.374 to 0.381 in., w/ 0.375 in. Distance from edge to hole cntr along width, 1.250 in. Distance from edge to hole cntr along width, 0.750 in. 14.02 hole diameter 0.374 to 0.381 in., w/ 0.375 in. Distance from edge to hole cntr along width, 1.250 in. Distance from edge to hole cntr along width, 0.750 in. 14.02 hole diameter 0.374 to 0.381 in., w/ 0.375 in. Distance from edge to hole cntr along width, 0.750 in. 15.02 hole diameter 0.374 to 0.381 in., w/ 0.375 in. Distance from edge to hole cntr along width, 0.750 in. 15.02 hole diameter 0.374 to 0.381 in., w/ 0.375 in. Distance from edge to hole cntr along width, 0.750 in. 16.02 hole diameter 0.374 to 0.381 in. 17.02 hole diameter 0.374 to 0.381 in. 17.02 hole diameter 0.374 to 0.375 in. 18.02 hole diameter 0.374 to 0.375 in. 19.	Mounting Method:
Left hand Closed Length: 14.125 inches Special Features: Has 2 hole diameter 0.374 to 0.381 in., w/ 0.375 in. Distance from edge to hole cntr along width, 1.250 in. Distance from edge to hole cntr along g & 2.000 in. Distance btwn hole cntrs; 4 holes diameter 0.165 to 0.171 in. Csk to diameter 0.284 x 100 degrees w/ c to c dist, along in the distance btwn hole cntrs; 4 holes diameter 0.165 to 0.171 in. Csk to diameter 0.284 x 100 degrees w/ c to c dist, along in the distance btwn hole cntrs; 4 holes diameter 0.165 to 0.171 in. Csk to diameter 0.284 x 100 degrees w/ c to c dist, along in the distance. For Application Data: An/uxc-4 Shelf Life: N/a Int of Measure: Demiltarization: No Fig:	Threaded hole
Closed Length: 14.125 inches Special Features: Has 2 hole diameter 0.374 to 0.381 in., w/ 0.375 in. Distance from edge to hole cntr along width, 1.250 in. Distance from edge to hole cntr along width, 1.250 in. Distance from edge to hole cntr along by 8 2.000 in. Distance btwn hole cntrs; 4 holes diameter 0.165 to 0.171 in. Csk to diameter 0.284 x 100 degrees w/ c to c dist, along width, 0.750 in. Fsc Application Data: An/uxc-4 Shelf Life: N/a Unit Of Measure: Deniliarization: No Fig:	Side For Which Designed:
14.125 inches 14	Left hand
Special Features: Has 2 hole diameter 0.374 to 0.381 in., w/ 0.375 in. Distance from edge to hole cntr along width, 1.250 in. Distance from edge to hole cntr along width, 1.250 in. Distance from edge to hole cntr along lg & 2.000 in. Distance btwn hole cntrs; 4 holes diameter 0.165 to 0.171 in. Csk to diameter 0.284 x 100 degrees w/ c to c dist, along width, 0.750 in. width, 0.750 in. Fsc Application Data: An/uxc-4 Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fig:	Closed Length:
Has 2 hole diameter 0.374 to 0.381 in., w/ 0.375 in. Distance from edge to hole ontr along width, 1.250 in. Distance from edge to hole ontr along lg & 2.000 in. Distance btwn hole ontrs; 4 holes diameter 0.165 to 0.171 in. Csk to diameter 0.284 x 100 degrees w/ c to c dist, along width, 0.750 in. Fsc Application Data: An/uxc-4 Shelf Life: N/a Unit Of Measure: Demilitarization: No	14.125 inches
along lg & 2.000 in. Distance btwn hole cntrs; 4 holes diameter 0.165 to 0.171 in. Csk to diameter 0.284 x 100 degrees w/ c to c dist, along width, 0.750 in. Fsc Application Data: An/uxc-4 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Special Features:
width, 0.750 in. Fsc Application Data: An/uxc-4 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Has 2 hole diameter 0.374 to 0.381 in., w/ 0.375 in. Distance from edge to hole cntr along width, 1.250 in. Distance from edge to hole cntr
Fsc Application Data: An/uxc-4 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	along Ig & 2.000 in. Distance btwn hole cntrs; 4 holes diameter 0.165 to 0.171 in. Csk to diameter 0.284 x 100 degrees w/ c to c dist, along
An/uxc-4 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	width, 0.750 in.
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Fsc Application Data:
N/a Unit Of Measure: Demilitarization: No Fiig:	An/uxc-4
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Fiig:	N/a
Demilitarization: No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
-	No
A03100	Fiig:
	A03100