NSN 5340-01-262-6633

Spacing Threaded Standoff - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-262-6633 **Thread Class:** 3b right external **Thread Direction:** Right-hand right external Thread Length: 0.5000 inches right external **Shoulder Diameter:** Between 0.3040 inches and 0.3160 inches **Shoulder Length:** 0.1250 inches **Second Shoulder Diameter:** 0.3470 inches **Second Shoulder Length:** 0.0800 inches Length: 0.7500 inches **Cross-sectional Shape:** Hexagon Width Across Flats: Between 0.3040 inches and 0.3160 inches Thready Qty Per Inch (tpi): 32 right external **Thread Size:** 0.1900 inches right external Material: Steel comp 4130 standoff or steel comp 4140 standoff or steel comp 8740 standoff or steel comp 8630 standoff **Material Specification:** Mil-s-6758 military specification single material response standoff or mil-s-5626 military specification single material response standoff or mil-s-6049 military specification single material response standoff or mil-s-6050 military specification single material response standoff **Surface Treatment:** Cadmium standoff and chromate standoff **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response standoff **Style Designator:** Two shoulders left internal and right external threads **Thread Series Designator:** Unjf right external Shelf Life:

Demilitarization:

Unit Of Measure:

No

N/a

NSN 5340-01-262-6633

Spacing Threaded Standoff - Page 2 of 2



Fiig:

A08900

Mil-std (military Standard):

Mil-s-6758 spec.