

View Online at <https://aerobasegroup.com/nsn/5340-01-263-2542>

**Mounting Hole Type:**

Plain and threaded

**First Leg Length:**

16.750 inches

**Second Leg Length:**

16.750 inches

**End Application:**

Carrier, persm-113a1, m-113a2, m113a3; chaparral/vulcan ads/ssamd; carrier, cargo 6-ton (m548 & m548a1)

**Second Leg Width:**

2.500 inches

**First Leg Hole Diameter:**

0.375 inches

**Second Leg Hole Diameter:**

1.560 inches

**Second Leg Distance Between Hole Centers Along Length:**

8.500 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

1.188 inches

**First Leg Thickness:**

0.375 inches

**Second Leg Thickness:**

0.375 inches

**First Leg Width:**

2.500 inches

**First Leg Distance From Edge To Hole Center Along Width:**

1.250 inches

**First Leg Distance From Edge To Hole Center Along Length:**

3.120 inches

**First Leg Distance Between First And Second Hole Centers Along Length:**

4.525 inches

**First Leg Distance Between Second And Third Hole Centers Along Length:**

4.470 inches

**First Leg Side Radius:**

1.000 inches

**Second Leg Side Radius:**

1.000 inches

**First Leg Style:**

Side radius

**First Leg Hole Arrangement Style:**

Three holes

**Second Leg Style:**

Side radius

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**Special Features:**

1st leg chamfered r side 45 deg; 2nd leg chamfered l side 30 deg, holespositioned 5.880 in. O/a c to l edge, 2.320 in. O/a c to r edge along lg

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0