

View Online at <https://aerobasegroup.com/nsn/5340-01-263-2542>

Mounting Hole Type:

Plain and threaded

First Leg Length:

16.750 inches

Second Leg Length:

16.750 inches

End Application:

Carrier, persm-113a1, m-113a2, m113a3; chaparral/vulcan ads/ssamd; carrier, cargo 6-ton (m548 & m548a1)

Second Leg Width:

2.500 inches

First Leg Hole Diameter:

0.375 inches

Second Leg Hole Diameter:

1.560 inches

Second Leg Distance Between Hole Centers Along Length:

8.500 inches

Second Leg Distance From Edge To Hole Center Along Width:

1.188 inches

First Leg Thickness:

0.375 inches

Second Leg Thickness:

0.375 inches

First Leg Width:

2.500 inches

First Leg Distance From Edge To Hole Center Along Width:

1.250 inches

First Leg Distance From Edge To Hole Center Along Length:

3.120 inches

First Leg Distance Between First And Second Hole Centers Along Length:

4.525 inches

First Leg Distance Between Second And Third Hole Centers Along Length:

4.470 inches

First Leg Side Radius:

1.000 inches

Second Leg Side Radius:

1.000 inches

First Leg Style:

Side radius

First Leg Hole Arrangement Style:

Three holes

Second Leg Style:

Side radius

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

Special Features:

1st leg chamfered r side 45 deg; 2nd leg chamfered l side 30 deg, holespositioned 5.880 in. O/a c to l edge, 2.320 in. O/a c to r edge along lg

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0