

View Online at <https://aerobasegroup.com/nsn/5340-01-264-0937>

Mounting Hole Type:

Plain and threaded

First Leg Length:

0.600 inches

Second Leg Length:

1.810 inches

Reinforcement Method (non-core):

Gusset one end

Second Leg Width:

20.750 inches

Second Leg Hole Diameter:

0.204 inches

Second Leg Distance Between Hole Centers Along Width:

18.375 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

4.875 inches

Second Leg Distance Between Second And Third Hole Centers Along Width:

6.500 inches

Second Leg Distance From Edge To Hole Center Along Width:

1.130 inches

Second Leg Distance From Edge To Hole Center Along Length:

1.022 inches

First Leg Thickness:

0.090 inches

Second Leg Thickness:

0.090 inches

First Leg Width:

20.750 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

No hole

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Four holes

Features Provided:

Nut

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Two clinch nuts ms3214-9 installed in end gusset 1.000 in. Apart; two clinch nuts ms3214-9 installed in second leg spaced 12.500 in. Apart

Material:

Aluminum alloy 5052

Material Specification:

Qq-a-250/8, h32 federal specification single material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541, cl 1a military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.