NSN 5340-01-264-5984

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-264-5984

Mounting Hole Type:
Counterbored and plain
First Leg Length:
4.000 inches
Second Leg Length:
4.000 inches
Second Leg Width:
22.000 inches
Second Leg End Width:
20.000 inches
Second Leg Distance Between First And Second Hole Centers Along Width:
3.250 inches
Second Leg Distance Between Second And Third Hole Centers Along Width:
1.625 inches
Second Leg Distance From Edge To Hole Center Along Width:
1.812 inches
Second Leg Distance From Edge To Hole Center Along Length:
2.540 inches
Second Leg Slot Length:
1.190 inches
Second Leg Slot Width:
0.562 inches
Second Leg Distance Between Third And Fourth Hole Centers Along Width:
1.625 inches
First Leg Thickness:
0.500 inches
Second Leg Thickness:
0.500 inches
First Leg Width:
22.000 inches
First Leg Distance Between Hole Centers Along Width:
2.125 inches
First Leg Distance Between Hole Centers Along Length:
1.000 inches
First Leg Distance From Edge To Hole Center Along Width:
0.750 inches
First Leg Distance From Edge To Hole Center Along Length:
1.125 inches
First Leg Style:
Square
Second Leg Style:
Chamfered ends

NSN 5340-01-264-5984 Angle Bracket - Page 2 of 2



Second Leg Relationship To First Leg:
Not identical
First Leg Angle:
90.0 degrees
Err Default:
Err default
Second Leg Chamfer Angle:
Between 40.0 degrees and 50.0 degrees
Special Features:
0.812 in. Sq holes e1ght places first leg; 1.062 in. W and 1.690 in. Lg holes two places second leg; color forest green
Material:
Aluminum alloy 6061
Material Specification:
Qq-a-200/16, t6 federal specification single material response
Surface Treatment:
Paint
Surface Treatment Specification:
Mil-f-14072, ps13.1, v military specification single treatment response
Style Designator:
Angle
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A042a0
Mil-std (military Standard):
Mil-f-14072 spec.