

View Online at <https://aerobasegroup.com/nsn/5340-01-264-5985>

Mounting Hole Type:

Counterbored and plain

First Leg Length:

4.000 inches

Second Leg Length:

4.000 inches

Second Leg Width:

27.620 inches

Second Leg End Width:

25.620 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

3.250 inches

Second Leg Distance Between Second And Third Hole Centers Along Width:

1.625 inches

Second Leg Distance From Edge To Hole Center Along Width:

5.687 inches

Second Leg Distance From Edge To Hole Center Along Length:

2.540 inches

Second Leg Slot Length:

1.190 inches

Second Leg Slot Width:

0.562 inches

Second Leg Distance Between Third And Fourth Hole Centers Along Width:

1.625 inches

First Leg Thickness:

0.500 inches

Second Leg Thickness:

0.500 inches

First Leg Width:

27.620 inches

First Leg Distance Between Hole Centers Along Width:

2.125 inches

First Leg Distance Between Hole Centers Along Length:

1.000 inches

First Leg Distance From Edge To Hole Center Along Width:

0.750 inches

First Leg Distance From Edge To Hole Center Along Length:

1.125 inches

First Leg Style:

Square

Second Leg Style:

Chamfered ends

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Err Default:

Err default

Second Leg Chamfer Angle:

Between 40.0 degrees and 50.0 degrees

Special Features:

1.062 in. W and 1.690 in lg slots 2nd leg, 0.812 in. Sq holes eight places 1st leg; color, forest green

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-200/16, t6 federal specification single material response

Surface Treatment:

Paint

Surface Treatment Specification:

Mil-f-14072, ps13.1, v military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-f-14072 spec.