## NSN 5340-01-265-0879

Access Cover - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-265-0879

| view Online at https://defobasegroup.com/nsh/3545-01-205-0073                     |
|---|
| Cross Sectional Shape:  |
| Recess, same shape as the periphery   |
| Width:  |
| Between 34.93 millimeters and 35.19 millimeters                                   |
| Flange Thickness:   |
| 8.13 millimeters  |
| Edge Shape:   |
| Rectangle, four holes   |
| Length:   |
| 91.95 millimeters   |
| Corner Radius:  |
| 1.5 millimeters   |
| Distance Between Holes Along Length:  |
| Between 60.32 millimeters and 60.58 millimeters                                   |
| Distance Between Holes Along Width:   |
| Between 26.81 millimeters and 27.07 millimeters                                   |
| Distance From First Hole Centerline To End Along Length:                          |
| 15.75 millimeters   |
| Distance From First Hole Centerline To End Along Width:                           |
| 4.060 millimeters   |
| First Recess Inside Height:   |
| 7.6 millimeters   |
| Body Thickness:   |
| 1.925 millimeters   |
| Securing Device Type:   |
| Special   |
| Mounting Opening Shape Style:   |
| Threaded hole   |
| Special Features:   |
| Dimension abku is along width; demension along length is 8.13 cm flange thickness |
| Material:   |
| Aluminum alloy 6061   |
| Material Specification:   |
| Qq-a-250/11, t6 federal specification single material response                    |
| Surface Treatment:  |
| Anodize   |
| Surface Treatment Specification:  |
| Mil-a-8625, t2, cl2 military specification single treatment response              |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |

--

## NSN 5340-01-265-0879

Access Cover - Page 2 of 2



Demilitarization:

No

Fiig:

A531c0

Mil-std (military Standard):

Mil-a-8625 spec.