

View Online at <https://aerobasegroup.com/nsn/5340-01-265-2142>

**Mounting Hole Type:**

Plain

**First Leg Length:**

1.500 inches

**Second Leg Length:**

4.000 inches

**Second Leg Width:**

38.500 inches

**First Leg Hole Diameter:**

Between 0.346 inches and 0.354 inches

**Second Leg Hole Diameter:**

Between 0.346 inches and 0.354 inches

**Second Leg Distance Between Hole Centers Along Width:**

16.500 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

18.000 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.500 inches

**First Leg Thickness:**

Between 0.115 inches and 0.135 inches

**Second Leg Thickness:**

Between 0.115 inches and 0.135 inches

**First Leg Width:**

38.500 inches

**First Leg Distance Between First And Second Hole Centers Along Width:**

19.250 inches

**First Leg Distance Between Second And Third Hole Centers Along Width:**

15.437 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.250 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.485 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

Three holes

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Material:**

Steel comp 1010 or steel comp 1011 or steel comp 1012 or steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020

**Surface Treatment:**

Paint

**Surface Treatment Specification:**

Mil-t-704 ty f military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-t-704 spec.