

View Online at <https://aerobasegroup.com/nsn/5340-01-265-2142>

Mounting Hole Type:

Plain

First Leg Length:

1.500 inches

Second Leg Length:

4.000 inches

Second Leg Width:

38.500 inches

First Leg Hole Diameter:

Between 0.346 inches and 0.354 inches

Second Leg Hole Diameter:

Between 0.346 inches and 0.354 inches

Second Leg Distance Between Hole Centers Along Width:

16.500 inches

Second Leg Distance From Edge To Hole Center Along Width:

18.000 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.500 inches

First Leg Thickness:

Between 0.115 inches and 0.135 inches

Second Leg Thickness:

Between 0.115 inches and 0.135 inches

First Leg Width:

38.500 inches

First Leg Distance Between First And Second Hole Centers Along Width:

19.250 inches

First Leg Distance Between Second And Third Hole Centers Along Width:

15.437 inches

First Leg Distance From Edge To Hole Center Along Width:

0.250 inches

First Leg Distance From Edge To Hole Center Along Length:

0.485 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Three holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 1010 or steel comp 1011 or steel comp 1012 or steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020

Surface Treatment:

Paint

Surface Treatment Specification:

Mil-t-704 ty f military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-t-704 spec.