

View Online at <https://aerobasegroup.com/nsn/5340-01-265-6184>

Mounting Hole Type:

Plain and threaded

First Leg Length:

1.500 inches

Second Leg Length:

1.500 inches

Second Leg Width:

4.120 inches

First Leg Slot Length:

0.620 inches

First Leg Slot Width:

Between 0.280 inches and 0.336 inches

Second Leg Hole Diameter:

Between 0.200 inches and 0.230 inches

Second Leg Distance Between Hole Centers Along Width:

0.600 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.710 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.880 inches

First Leg Thickness:

0.125 inches

Second Leg Thickness:

0.125 inches

First Leg Width:

4.120 inches

First Leg Distance Between Hole Centers Along Width:

2.855 inches

First Leg Distance From Edge To Hole Center Along Width:

0.620 inches

First Leg Distance From Edge To Hole Center Along Length:

0.620 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

2 slots

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Second leg includes 0.190-24 unc 2b nut and 0.125 in. Square plate

Material:

Aluminum alloy 5083 or aluminum alloy 5086

Material Specification:

Qq-a-200/4 h111 federal specification 1st material response or qq-a-200/5 h111 federal specification 2nd material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541 class 1a military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.