

View Online at <https://aerobasegroup.com/nsn/5340-01-266-1087>

Cross Sectional Shape:

Recess, other than round

Hole Diameter:

Between 0.057 inches and 0.062 inches

Width:

5.374 inches

Flange Thickness:

1.067 inches

Length:

5.874 inches

Inside Width:

3.240 inches

Inside Length:

3.740 inches

Distance Between Holes Along Length:

0.914 inches

Distance Between Holes Along Width:

1.466 inches

Distance Between Hole Centerline And First Hole Along Width:

1.146 inches

Distance From First Hole Centerline To End Along Length:

0.594 inches

Distance From First Hole Centerline To End Along Width:

0.469 inches

First Recess Inside Height:

0.060 inches

Securing Device Type:

Special

Mounting Opening Shape Style:

Unthreaded hole

Special Features:

Four threaded holes 0.164-32 unc-3b on 2.750 in. By 3.936 mtg centers; ten mtg holes counterbored and reamed 0.500 in. Dp, 0.3125 in. Min 0.3165 in. Maximum diameter w/100.0 degrees countersink to 0.625 in. Dia; one surf only w/fuel resistant coating gss 4.303m, grumman aircraft

Material:

Aluminum alloy 7075

Material Specification:

Qq-a-250/12, t6 federal specification single material response

Surface Treatment:

Primer zinc chromate

Surface Treatment Specification:

Gss9.010, grumman aircraft mfr ref single treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A531c0