

View Online at <https://aerobasegroup.com/nsn/5340-01-266-3863>

**Mounting Hole Type:**

Plain

**First Leg Length:**

3.500 inches

**Second Leg Length:**

4.250 inches

**Second Leg Width:**

4.250 inches

**Second Leg End Width:**

3.750 inches

**First Leg Hole Diameter:**

0.406 inches

**Second Leg Hole Diameter:**

0.625 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.750 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.750 inches

**First Leg Thickness:**

0.250 inches

**Second Leg Thickness:**

0.250 inches

**First Leg Width:**

4.250 inches

**First Leg Distance Between Hole Centers Along Width:**

1.750 inches

**First Leg Distance Between Hole Centers Along Length:**

1.000 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.690 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.500 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Chamfered ends

**Second Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Second Leg Chamfer Angle:**

Between 40.0 degrees and 50.0 degrees

**Special Features:**

1st leg has a cut corner 0.250 in. X 45.0 deg, 1 pl

**Material:**

Aluminum alloy 6061

**Material Specification:**

Qq-a-200/8, t6 federal specification single material response

**Surface Treatment:**

Paint

**Surface Treatment Specification:**

Mil-c-22750 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-c-22750 spec.