

View Online at <https://aerobasegroup.com/nsn/5340-01-266-4953>

Mounting Hole Type:

Plain

First Leg Length:

38.0 millimeters

Second Leg Length:

63.0 millimeters

Second Leg Width:

200.0 millimeters

First Leg Hole Diameter:

Between 5.950 millimeters and 6.203 millimeters

Second Leg Hole Diameter:

Between 10.450 millimeters and 10.703 millimeters

Second Leg Distance Between Hole Centers Along Width:

150.0 millimeters

Second Leg Distance Between First And Second Hole Centers Along Width:

50.0 millimeters

Second Leg Distance Between Second And Third Hole Centers Along Width:

50.0 millimeters

Second Leg Distance From Edge To Hole Center Along Width:

25.0 millimeters

Second Leg Distance From Edge To Hole Center Along Length:

18.0 millimeters

First Leg Thickness:

3.17 millimeters

Second Leg Thickness:

3.17 millimeters

First Leg Width:

200.0 millimeters

First Leg Distance Between Hole Centers Along Width:

100.0 millimeters

First Leg Distance Between First And Second Hole Centers Along Width:

37.5 millimeters

First Leg Distance Between Second And Third Hole Centers Along Width:

37.5 millimeters

First Leg Distance From Edge To Hole Center Along Width:

12.5 millimeters

First Leg Distance From Edge To Hole Center Along Length:

12.5 millimeters

First Leg Style:

Square

Second Leg Style:

Square

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Two additional holes in first leg 5.950 mm min 6.203 mm maximum dia; eight additional holes in second leg 4.450 mm min 4.627 mm maximum dia

Material:

Aluminum alloy 5083

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541, cl 1a military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.