NSN 5340-01-266-4953

Angle Bracket - Page 1 of 2

Mounting Hole Type:

Plain

View Online at https://aerobasegroup.com/nsn/5340-01-266-4953



First Leg Length:
38.0 millimeters
Second Leg Length:
63.0 millimeters
Second Leg Width:
200.0 millimeters
First Leg Hole Diameter:
Between 5.950 millimeters and 6.203 millimeters
Second Leg Hole Diameter:
Between 10.450 millimeters and 10.703 millimeters
Second Leg Distance Between Hole Centers Along Width:
150.0 millimeters
Second Leg Distance Between First And Second Hole Centers Along Width:
50.0 millimeters
Second Leg Distance Between Second And Third Hole Centers Along Width:
50.0 millimeters
Second Leg Distance From Edge To Hole Center Along Width:
25.0 millimeters
Second Leg Distance From Edge To Hole Center Along Length:
18.0 millimeters
First Leg Thickness:
3.17 millimeters
Second Leg Thickness:
3.17 millimeters
First Leg Width:
200.0 millimeters
First Leg Distance Between Hole Centers Along Width:
100.0 millimeters
First Leg Distance Between First And Second Hole Centers Along Width:
37.5 millimeters
First Leg Distance Between Second And Third Hole Centers Along Width:
37.5 millimeters
First Leg Distance From Edge To Hole Center Along Width:
12.5 millimeters
First Leg Distance From Edge To Hole Center Along Length:
12.5 millimeters
First Leg Style:
Square
Second Leg Style:
Square

# NSN 5340-01-266-4953

Angle Bracket - Page 2 of 2



# Second Leg Relationship To First Leg:

Not identical

## First Leg Angle:

90.0 degrees

## Special Features:

Two additional holes in first leg 5.950 mm min 6.203 mm maximum dia; eight additional holes in second leg 4.450 mm min 4.627 mm

maximum dia

Material:

Aluminum alloy 5083

#### Surface Treatment:

Chromate

# Surface Treatment Specification:

Mil-c-5541, cl 1a military specification single treatment response

### Style Designator:

Angle

# Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No

## Fiig:

A042a0

## Mil-std (military Standard):

Mil-c-5541 spec.