NSN 5340-01-266-5869

Access Cover - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-266-5869

| view Offilite at https://aerobasegroup.com/hist//3540-01-200-3003 |
|---|
| Cross Sectional Shape: |
| Flat |
| Hole Diameter: |
| 0.144 inches and 0.195 inches |
| Width: |
| 6.400 inches |
| Edge Shape: |
| Rectangle, multi holes |
| Length: |
| Between 27.420 inches and 27.460 inches |
| Corner Radius: |
| 0.250 inches |
| Hole Quantity Along Length: |
| 10 |
| Hole Quantity Along Width: |
| 4 |
| Distance Between Holes Along Length: |
| 4.320 inches and 4.460 inches |
| Distance From First Hole Centerline To End Along Length: |
| Between 0.330 inches and 0.350 inches |
| Distance From First Hole Centerline To End Along Width: |
| Between 0.300 inches and 0.310 inches |
| Body Thickness: |
| 0.063 inches |
| Securing Device Type: |
| Turnlock fastener and threaded fastener |
| End Application: |
| Alq-17 (v) 1 |
| Features Provided: |
| Special marking |
| Special Features: |
| 7 mtg holes csk 100 degrees nearside diameter 0.279 to 0.301 in.; item requires 7 turnlock fastener studs p/n 2137240g004, 7 turnlock |
| fastener eyelets p/n 2135202g002, 7 modified screws p/n 2612130g001, 7 ring retainers p/n 2136796g002, 4 rfi gaskets p/n 2614894g001 |
| 002, 003 & 004 |
| Material: |
| Aluminum alloy 6061 |
| Material Specification: |
| Qq-a-250/11 federal specification single material response |
| Surface Treatment: |
| Chromate and primer zinc chromate and paint |
| Surface Treatment Specification: |

Mil-c-5541, class 1a military specification 1st treatment response and mil-p-8585 military specification 2nd treatment response and tt-e-527

Shelf Life:

federal specification 3rd treatment response

NSN 5340-01-266-5869

Access Cover - Page 2 of 2



| ι | Jnit | Of | Measure: |
|---|-------|----|-----------|
| • | ,,,,, | • | moudai c. |

--

Demilitarization:

No

Fiig:

A531c0

Mil-std (military Standard):

Mil-c-5541 spec.