

View Online at <https://aerobasegroup.com/nsn/5340-01-266-5869>

**Cross Sectional Shape:**

Flat

**Hole Diameter:**

0.144 inches and 0.195 inches

**Width:**

6.400 inches

**Edge Shape:**

Rectangle, multi holes

**Length:**

Between 27.420 inches and 27.460 inches

**Corner Radius:**

0.250 inches

**Hole Quantity Along Length:**

10

**Hole Quantity Along Width:**

4

**Distance Between Holes Along Length:**

4.320 inches and 4.460 inches

**Distance From First Hole Centerline To End Along Length:**

Between 0.330 inches and 0.350 inches

**Distance From First Hole Centerline To End Along Width:**

Between 0.300 inches and 0.310 inches

**Body Thickness:**

0.063 inches

**Securing Device Type:**

Turnlock fastener and threaded fastener

**End Application:**

Alq-17 (v) 1

**Features Provided:**

Special marking

**Special Features:**

7 mtg holes csk 100 degrees nearside diameter 0.279 to 0.301 in.; item requires 7 turnlock fastener studs p/n 2137240g004, 7 turnlock fastener eyelets p/n 2135202g002, 7 modified screws p/n 2612130g001, 7 ring retainers p/n 2136796g002, 4 rfi gaskets p/n 2614894g001, 002, 003 & 004

**Material:**

Aluminum alloy 6061

**Material Specification:**

Qq-a-250/11 federal specification single material response

**Surface Treatment:**

Chromate and primer zinc chromate and paint

**Surface Treatment Specification:**

Mil-c-5541, class 1a military specification 1st treatment response and mil-p-8585 military specification 2nd treatment response and tt-e-527 federal specification 3rd treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A531c0

**Mil-std (military Standard):**

Mil-c-5541 spec.