NSN 5340-01-266-5869

Access Cover - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-266-5869

view Offilite at https://aerobasegroup.com/hist//3540-01-200-3003
Cross Sectional Shape:
Flat
Hole Diameter:
0.144 inches and 0.195 inches
Width:
6.400 inches
Edge Shape:
Rectangle, multi holes
Length:
Between 27.420 inches and 27.460 inches
Corner Radius:
0.250 inches
Hole Quantity Along Length:
10
Hole Quantity Along Width:
4
Distance Between Holes Along Length:
4.320 inches and 4.460 inches
Distance From First Hole Centerline To End Along Length:
Between 0.330 inches and 0.350 inches
Distance From First Hole Centerline To End Along Width:
Between 0.300 inches and 0.310 inches
Body Thickness:
0.063 inches
Securing Device Type:
Turnlock fastener and threaded fastener
End Application:
Alq-17 (v) 1
Features Provided:
Special marking
Special Features:
7 mtg holes csk 100 degrees nearside diameter 0.279 to 0.301 in.; item requires 7 turnlock fastener studs p/n 2137240g004, 7 turnlock
fastener eyelets p/n 2135202g002, 7 modified screws p/n 2612130g001, 7 ring retainers p/n 2136796g002, 4 rfi gaskets p/n 2614894g001
002, 003 & 004
Material:
Aluminum alloy 6061
Material Specification:
Qq-a-250/11 federal specification single material response
Surface Treatment:
Chromate and primer zinc chromate and paint
Surface Treatment Specification:

Mil-c-5541, class 1a military specification 1st treatment response and mil-p-8585 military specification 2nd treatment response and tt-e-527

Shelf Life:

federal specification 3rd treatment response

NSN 5340-01-266-5869

Access Cover - Page 2 of 2



ι	Jnit	Of	Measure:
•	,,,,,	•	moudai c.

--

Demilitarization:

No

Fiig:

A531c0

Mil-std (military Standard):

Mil-c-5541 spec.