

View Online at <https://aerobasegroup.com/nsn/5340-01-269-4111>

End Application:

F-16 c/d common

Special Features:

94130 steel per ams 6350 or 1050 steel per ams 5085, ti-cad plate per cps 6708, 0.0005 to 0.0008 in. Thk or vac-cad plate per mil-c-8837 type 2, cl 1 0.0005 to 0.0008 thk w/ supplementary chromate trtmt, external surfaces primed w/ 1 coat of primer per cps 6964 0.0006 to 0.0009 in. Thk; oa lg 1.260 in., width 0.620 in., 0.050 in. Thk; item has 2 holes diameter 0.098 to 0.103 in. C to c distance 0.239 to 0.241 in., dist from edge to hole cntr along lg 0.630 in.; item also has 2 splines per ms33787 wrench no. 8, c to c distance btwn splines along lg 0.737 to 0.743 in., dist from edge to cntr along width 0.305 to 0.315, dist btwn spline cntr & hole cntr along lg 0.368 to 0.372 in., dist btwn spline cntr & hole cntr along width 0.118 to 0.122 in.; item is chamfered 0.120 x 45 deg

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A042a0