## NSN 5340-01-269-7565

Double Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-269-7565 **Mounting Hole Type:** Plain First Leg Length: 0.373 inches Second Leg Length: 0.990 inches Second Leg Width: 1.220 inches Second Leg End Width: 0.980 inches First Leg Hole Diameter: Between 0.098 inches and 0.106 inches Second Leg Hole Diameter: Between 0.143 inches and 0.149 inches Second Leg Distance Between Hole Centers Along Width: 0.940 inches Second Leg Distance Between Hole Centers Along Length: 0.540 inches Second Leg Distance From Edge To Hole Center Along Width: 0.140 inches Second Leg Distance From Edge To Hole Center Along Length: 0.200 inches First Leg Thickness: 0.063 inches Second Leg Thickness: 0.063 inches **Center Section Height:** 0.413 inches **Center Section Width:** 1.220 inches **Center Section Thickness:** 0.063 inches First Leg Width: 1.220 inches First Leg Distance Between Hole Centers Along Width: 0.722 inches First Leg Distance From Edge To Hole Center Along Width: 0.250 inches First Leg Distance From Edge To Hole Center Along Length: 0.125 inches First Leg Style:

Square

## NSN 5340-01-269-7565

Double Angle Bracket - Page 2 of 2



First Leg Hole Arrangement Style:
Two holes
Second Leg Style:
Chamfered ends
Second Leg Hole Arrangement Style:
Two holes
Second Leg Relationship To First Leg:
Not identical
First Leg Angle:
90.0 degrees
Second Leg Angle:
90.0 degrees
Second Leg Chamfer Angle:
45.0 degrees
Material:
Aluminum alloy 5052
Material Specification:
Qq-a-250/8, temp h32 federal specification single material response
Surface Treatment:
Chromate
Surface Treatment Specification:
Mil-c-5541, cl 3 military specification single treatment response
Style Designator:
Double angle
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A042a0
Mil-std (military Standard):
Mil-c-5541 spec.