NSN 5340-01-271-4364

Double Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-271-4364

First Leg Length:					
0.400 inches					
Second Leg Length:					
0.400 inches					
First Leg Thickness:					
Between 0.037 inches and 0.043 inches					
Second Leg Thickness:					
Between 0.037 inches and 0.043 inches					
Center Section Height:					
1.290 inches					
Center Section Width:					
0.500 inches					
Center Section Thickness:					
Between 0.037 inches and 0.043 inches					
First Leg Width:					
0.500 inches					
First Leg Style:					
Square					
First Leg Hole Arrangement Style:					
No hole					
Features Provided:					
Nut					
Second Leg Relationship To First Leg:					
Identical					
Identical First Leg Angle:					
First Leg Angle:					
First Leg Angle: 90.0 degrees					
First Leg Angle: 90.0 degrees Second Leg Angle:					
First Leg Angle: 90.0 degrees Second Leg Angle: 90.0 degrees					
First Leg Angle: 90.0 degrees Second Leg Angle: 90.0 degrees Special Features:					
First Leg Angle: 90.0 degrees Second Leg Angle: 90.0 degrees Special Features: Two clinch nuts on center leg spaced 0.650 in. Apart					
First Leg Angle: 90.0 degrees Second Leg Angle: 90.0 degrees Special Features: Two clinch nuts on center leg spaced 0.650 in. Apart Material:					
First Leg Angle: 90.0 degrees Second Leg Angle: 90.0 degrees Special Features: Two clinch nuts on center leg spaced 0.650 in. Apart Material: Aluminum alloy 5052					
First Leg Angle: 90.0 degrees Second Leg Angle: 90.0 degrees Special Features: Two clinch nuts on center leg spaced 0.650 in. Apart Material: Aluminum alloy 5052 Material Specification:					
First Leg Angle: 90.0 degrees Second Leg Angle: 90.0 degrees Special Features: Two clinch nuts on center leg spaced 0.650 in. Apart Material: Aluminum alloy 5052 Material Specification: Qq-a-250/8, h32 federal specification single material response					
First Leg Angle: 90.0 degrees Second Leg Angle: 90.0 degrees Special Features: Two clinch nuts on center leg spaced 0.650 in. Apart Material: Aluminum alloy 5052 Material Specification: Qq-a-250/8, h32 federal specification single material response Surface Treatment:					
First Leg Angle: 90.0 degrees Second Leg Angle: 90.0 degrees Special Features: Two clinch nuts on center leg spaced 0.650 in. Apart Material: Aluminum alloy 5052 Material Specification: Qq-a-250/8, h32 federal specification single material response Surface Treatment: Chromate					
First Leg Angle: 90.0 degrees Second Leg Angle: 90.0 degrees Special Features: Two clinch nuts on center leg spaced 0.650 in. Apart Material: Aluminum alloy 5052 Material Specification: Qq-a-250/8, h32 federal specification single material response Surface Treatment: Chromate Surface Treatment Specification:					
First Leg Angle: 90.0 degrees Second Leg Angle: 90.0 degrees Special Features: Two clinch nuts on center leg spaced 0.650 in. Apart Material: Aluminum alloy 5052 Material Specification: Qq-a-250/8, h32 federal specification single material response Surface Treatment: Chromate Surface Treatment Specification: Mil-c-5541 military specification single treatment response					
First Leg Angle: 90.0 degrees Second Leg Angle: 90.0 degrees Special Features: Two clinch nuts on center leg spaced 0.650 in. Apart Material: Aluminum alloy 5052 Material Specification: Qq-a-250/8, h32 federal specification single material response Surface Treatment: Chromate Surface Treatment Specification: Mil-c-5541 military specification single treatment response Style Designator:					

NSN 5340-01-271-4364

Double Angle Bracket - Page 2 of 2



	ι	Jn	it	Of	Measure:
--	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.