

View Online at <https://aerobasegroup.com/nsn/5340-01-272-7492>

**Mounting Hole Type:**

Plain

**First Leg Length:**

0.750 inches

**Second Leg Length:**

1.000 inches

**Second Leg Width:**

5.700 inches

**Second Leg Corner Radius:**

0.250 inches

**First Leg Hole Diameter:**

Between 0.095 inches and 0.100 inches

**Second Leg Hole Diameter:**

Between 0.256 inches and 0.263 inches

**Second Leg Distance Between Hole Centers Along Width:**

5.200 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.250 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.330 inches

**First Leg Thickness:**

0.063 inches

**Second Leg Thickness:**

0.063 inches

**First Leg Width:**

5.700 inches

**First Leg Distance Between Hole Centers Along Width:**

2.500 inches

**First Leg Distance From Edge To Hole Center Along Width:**

1.600 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.147 inches

**First Leg Style:**

Cut out

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Corner radius

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**First Leg Cutout Length:**

0.397 inches

**First Leg Cutout Width:**

2.320 inches

**Special Features:**

First leg chamfered corners 0.600 by 45 deg

**Material:**

Aluminum alloy 6061

**Material Specification:**

Qq-a-200/8, t6 federal specification single material response

**Surface Treatment:**

Chromate

**Surface Treatment Specification:**

Mil-c-5541, cl 2 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-c-5541 spec.