

View Online at <https://aerobasegroup.com/nsn/5340-01-272-9107>

Mounting Hole Type:

Counterbored and plain

First Leg Length:

2.500 inches

Second Leg Length:

5.500 inches

Reinforcement Method (non-core):

Gusset both legs

Second Leg Width:

14.750 inches

First Leg Hole Diameter:

0.316 inches

Second Leg Hole Diameter:

0.281 inches

Second Leg Distance Between Hole Centers Along Width:

11.750 inches

Second Leg Distance Between Hole Centers Along Length:

2.188 inches

Second Leg Distance From Edge To Hole Center Along Width:

1.500 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.812 inches

First Leg Thickness:

0.125 inches

Second Leg Thickness:

0.125 inches

First Leg Width:

14.750 inches

First Leg Distance Between Hole Centers Along Width:

12.750 inches

First Leg Distance Between First And Second Hole Centers Along Width:

4.000 inches

First Leg Distance Between Second And Third Hole Centers Along Width:

4.750 inches

First Leg Distance From Edge To Hole Center Along Width:

0.516 inches

First Leg Distance From Edge To Hole Center Along Length:

0.344 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Four holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Four holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Includes four captive screws and eight washers; dash 02 is opposite of dash 01

Material:

Aluminum alloy 6061

Material Specification:

110-5010-001, t6, caged 97871 mfr ref single material response

Surface Treatment:

Paint

Surface Treatment Specification:

401-27549, caged 97871 mfr ref single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0