# NSN 5340-01-273-0027

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-273-0027

Mounting Hole Type:
Plain and threaded
First Leg Length:
0.512 inches
Second Leg Length:
1.000 inches
Second Leg Width:
2.718 inches
First Leg Hole Diameter:
0.112 inches
Second Leg Hole Diameter:
0.130 inches
Second Leg Distance Between Hole Centers Along Width:
2.000 inches
Second Leg Distance Between First And Second Hole Centers Along Width:
0.500 inches
Second Leg Distance Between Second And Third Hole Centers Along Width:
0.500 inches
Second Leg Distance From Edge To Hole Center Along Width:
0.360 inches
Second Leg Distance From Edge To Hole Center Along Length:
0.380 inches
First Leg Thickness:
0.063 inches
Second Leg Thickness:
0.063 inches
First Leg Width:
2.718 inches
First Leg Distance Between Hole Centers Along Width:
2.500 inches
First Leg Distance From Edge To Hole Center Along Width:
0.109 inches
First Leg Distance From Edge To Hole Center Along Length:
0.270 inches
First Leg Style:
Cut out
First Leg Hole Arrangement Style:
Two holes
Second Leg Style:
Square
Second Leg Relationship To First Leg:
Not identical

# NSN 5340-01-273-0027

Angle Bracket - Page 2 of 2



#### First Leg Angle:

90.0 degrees

### First Leg Cutout Length:

0.512 inches

# First Leg Cutout Width:

2.298 inches

# **Special Features:**

Second leg has a 2.298 in. By 0.450 in. Opening extending into first leg

#### Material:

Aluminum alloy 5052

#### **Material Specification:**

Qq-a-250/8, temp h32 federal specification single material response

#### Surface Treatment:

Chromate

#### Surface Treatment Specification:

Mil-c-5541, cl 3 military specification single treatment response

#### Style Designator:

Angle

#### Shelf Life:

N/a

# Unit Of Measure:

--

# Demilitarization:

No

# Fiig:

A042a0

# Mil-std (military Standard):

Mil-c-5541 spec.