

View Online at <https://aerobasegroup.com/nsn/5340-01-273-1683>

Mounting Hole Type:

Countersunk and plain and threaded

First Leg Length:

6.470 inches

Second Leg Length:

8.540 inches

Reinforcement Method (non-core):

Turned edge both legs

Second Leg Width:

0.450 inches

First Leg Hole Diameter:

0.166 inches

Second Leg Hole Diameter:

0.150 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.200 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.200 inches

First Leg Thickness:

0.220 inches

Second Leg Thickness:

0.120 inches

First Leg Width:

0.450 inches

First Leg Distance From Edge To Hole Center Along Width:

0.200 inches

First Leg Distance From Edge To Hole Center Along Length:

0.200 inches

First Leg Style:

Extended flat

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Extended flat

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Two 0.166 in. By 0.366 in. Slots located on turned edge of second leg

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-250/11 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 2, cl 2 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A042a0

Mil-std (military Standard):

Mil-a-8625 spec.