

View Online at <https://aerobasegroup.com/nsn/5340-01-273-9335>

**Width:**

Between 0.531 inches and 0.594 inches

**Overall Height:**

Between 0.891 inches and 1.010 inches

**Material Thickness:**

0.030 inches

**Length:**

Between 0.490 inches and 0.547 inches

**Mounting Method:**

Unthreaded hole

**Distance From Loop Center To End:**

Between 0.719 inches and 0.781 inches

**Special Features:**

Clip top corners are radiused at 0.031 in. Min.-0.070 in. Max. On a 19.0-21.0 deg. Angle; clip ends at opening turn outward at 14.0-16.0 deg. From clip center line; clip grip dia. At closure is 0.141 in. Min.-0.180 in. Max.; clip top is radiused on all four corners at 0.016 in. Min.-0.062 in. Max., at 0.062 in. Min.-0.125 in. Max. From length edge and 0.013 in. Min.-0.188 in. Max. From width edge; mounting holes are centered at 0.240 in. Min.-0.281 in. Max. From length edge and 0.100 in. Min.-0.141 in. Max. From width edge; unit is heat treated per mil-h-6875, soln and age hardened to 33-38 rockwell c

**Material:**

Steel

**Material Specification:**

Dtd 189 mfr ref single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Mil-std-171, finish no. 5.4.1 military standard single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A03100

**Mil-std (military Standard):**

Mil-std-171 spec.