

View Online at <https://aerobasegroup.com/nsn/5340-01-274-7297>

Mounting Hole Type:

Plain

First Leg Length:

Between 0.570 inches and 0.600 inches

Second Leg Length:

Between 0.920 inches and 0.950 inches

Reinforcement Method (non-core):

Gusset both sides

Second Leg Width:

Between 3.980 inches and 4.020 inches

First Leg Hole Diameter:

Between 0.218 inches and 0.226 inches

First Leg Thickness:

0.040 inches

Second Leg Thickness:

0.040 inches

First Leg Width:

Between 3.980 inches and 4.020 inches

First Leg Distance Between First And Second Hole Centers Along Width:

1.276 inches

First Leg Distance Between Second And Third Hole Centers Along Width:

1.276 inches

First Leg Distance From Edge To Hole Center Along Width:

0.724 inches

First Leg Distance From Edge To Hole Center Along Length:

0.240 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Three holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

No hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-250/11, alloy 6061-t4 federal specification single material response

Surface Treatment:

Paint

Surface Treatment Specification:

F+5025, type 27, cl c, garrett turbine engine co mfr ref single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A042a0