

View Online at <https://aerobasegroup.com/nsn/5340-01-274-7297>

**Mounting Hole Type:**

Plain

**First Leg Length:**

Between 0.570 inches and 0.600 inches

**Second Leg Length:**

Between 0.920 inches and 0.950 inches

**Reinforcement Method (non-core):**

Gusset both sides

**Second Leg Width:**

Between 3.980 inches and 4.020 inches

**First Leg Hole Diameter:**

Between 0.218 inches and 0.226 inches

**First Leg Thickness:**

0.040 inches

**Second Leg Thickness:**

0.040 inches

**First Leg Width:**

Between 3.980 inches and 4.020 inches

**First Leg Distance Between First And Second Hole Centers Along Width:**

1.276 inches

**First Leg Distance Between Second And Third Hole Centers Along Width:**

1.276 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.724 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.240 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

Three holes

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

No hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Material:**

Aluminum alloy 6061

**Material Specification:**

Qq-a-250/11, alloy 6061-t4 federal specification single material response

**Surface Treatment:**

Paint

**Surface Treatment Specification:**

F+5025, type 27, cl c, garrett turbine engine co mfr ref single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A042a0