

View Online at <https://aerobasegroup.com/nsn/5340-01-276-1735>

Mounting Hole Type:

Plain and threaded

First Leg Length:

0.430 inches

Second Leg Length:

0.512 inches

Second Leg Width:

0.430 inches

First Leg Hole Diameter:

0.109 inches

Second Leg Hole Diameter:

0.112 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.210 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.212 inches

First Leg Thickness:

0.080 inches

Second Leg Thickness:

0.430 inches

Center Section Height:

0.268 inches

Center Section Width:

0.430 inches

Center Section Thickness:

0.080 inches

First Leg Width:

1.000 inches

First Leg Distance Between First And Second Hole Centers Along Width:

0.400 inches

First Leg Distance Between Second And Third Hole Centers Along Width:

0.400 inches

First Leg Distance From Edge To Hole Center Along Width:

0.100 inches

First Leg Distance From Edge To Hole Center Along Length:

0.150 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Three holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Angle:

90.0 degrees

Material:

Aluminum alloy 2024

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625 cl 2 military specification single treatment response

Style Designator:

Double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-a-8625 spec.