Spacing Threaded Standoff - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5340-01-276-5732

Thread Class:

2b left internal (includes through thread)

Thread Direction:

Right-hand left internal (includes through thread)

Thread Length:

1.8800 inches left internal (includes through thread)

Length:

1.8800 inches

Cross-sectional Shape:

Hexagon

Width Across Flats:

Between 0.5520 inches and 0.5620 inches

Thready Qty Per Inch (tpi):

16 left internal (includes through thread)

Thread Size:

0.3750 inches left internal (includes through thread)

Material:

Steel comp 1015 standoff or steel comp 1016 standoff or steel comp 1017 standoff or steel comp 1018 standoff or steel comp 1019 standoff or steel comp 1020 standoff or steel comp 1021 standoff or steel comp 1022 standoff or steel comp 1023 standoff or steel comp 1025 standoff or steel comp 1211 standoff or steel comp 1212 standoff or steel comp 1213 standoff or steel comp 1215 standoff

Material Specification:

Astm-a-108 assn standard single material response or qq-s-637 federal specification single material response

Surface Treatment:

Paint standoff or phosphate zinc standoff

Surface Treatment Specification:

Tt-c-490, type 1 or type 3 federal specification single treatment response standoff

Style Designator:

Internally threaded full length

Thread Series Designator:

Unc left internal (includes through thread)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A08900