

View Online at <https://aerobasegroup.com/nsn/5340-01-276-7525>

**Mounting Hole Type:**

Plain

**First Leg Length:**

1.000 inches

**Second Leg Length:**

1.000 inches

**Second Leg Width:**

4.750 inches

**First Leg Hole Diameter:**

0.199 inches

**Second Leg Hole Diameter:**

3.750 inches

**Second Leg Distance Between First And Second Hole Centers Along Width:**

1.875 inches

**Second Leg Distance Between Second And Third Hole Centers Along Width:**

1.875 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.500 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.380 inches

**First Leg Thickness:**

0.063 inches

**Second Leg Thickness:**

0.063 inches

**Center Section Height:**

3.870 inches

**Center Section Width:**

4.750 inches

**Center Section Thickness:**

0.063 inches

**First Leg Width:**

2.880 inches

**First Leg Distance Between Hole Centers Along Width:**

2.039 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.420 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.380 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

Three holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Second Leg Angle:**

90.0 degrees

**Material:**

Aluminum alloy 2024

**Material Specification:**

Qq-a-250/5, t3 federal specification single material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625 military specification single treatment response

**Style Designator:**

Adjacent angles

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0

**Mil-std (military Standard):**

Mil-a-8625 spec.