

View Online at <https://aerobasegroup.com/nsn/5340-01-277-4428>

Mounting Hole Type:

Plain and threaded

First Leg Length:

1.300 inches

Second Leg Length:

1.400 inches

Second Leg Width:

3.000 inches

First Leg Hole Diameter:

0.250 inches

Second Leg Hole Diameter:

0.250 inches

Second Leg Distance From Edge To Hole Center Along Width:

1.500 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.500 inches

First Leg Thickness:

0.250 inches

Second Leg Thickness:

0.250 inches

Center Section Height:

Between 1.240 inches and 1.250 inches

Center Section Width:

3.000 inches

Center Section Thickness:

0.350 inches

First Leg Width:

3.000 inches

First Leg Distance From Edge To Hole Center Along Width:

1.500 inches

First Leg Distance From Edge To Hole Center Along Length:

0.700 inches

First Leg Style:

Chamfered ends

First Leg Hole Arrangement Style:

One hole

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Angle:

90.0 degrees

First Leg Chamfer Angle:

30.0 degrees

Special Features:

Center section has three holes 0.212 in. Min, 0.218 in. Max

Material:

Aluminum alloy 2024 or aluminum alloy 6061

Material Specification:

Qq-a-225/6, t351 federal specification 1st material response or qq-a-200/8, t6511 federal specification 2nd material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 1, cl 1 military specification single treatment response

Style Designator:

Double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-a-8625 spec.